



PRODUCT DATA SHEET

09NS Series Track Marking Paint

PRODUCT DESCRIPTION:

Water based air dry, self cross-linking acrylic non-slip paint for road racing circuits

INTENDED USES:

Highly visible, anti-slip track marking paint for asphalt and concrete roadway, curbing and pit lane markings.

PHYSICAL PROPERTIES:

Vehicle Type:	Acrylic Resin
Color:	Make to Order
Finish:	Flat & Abrasive
Solids	
By Volume:	50% Avg. (+/-2%)
By Weight:	60% Avg.
Viscosity:	20-25 sec / Zahn 3
V.O.C.	Less than 100 grams per litre
Pot Life	N/A
Recommended Dry Film Thickness:	5-6 mils
Theoretical Coverage:	120-150 sq.ft. per gal.(smooth surface) 360-450 ln.ft. per gal (4" stripe)

DRY TIME @ 77° F

Tack Free	15-30 mins.
Return to Service	1 hour
Recoat	Infinite

NOTE:

SURFACE PREPARATION:

Surfaces that are to be coated must be clean, dry and free of surface contaminants. For best performance, pressure wash areas that are to be coated with a minimum of 1500psi water pressure.

THINNING: Use only clean water.

Brush/Roll – Not recommended.
Conventional – Reduce up to 5%.

APPLICATION:

Conventional Pressure feed line striping machine, Kelly-Creswell HDC Line Painter
Brush/Roll

CLEANING UP:

Water

ORDERING:

These products are available in 4 gallons pails

COMPLIANCE: Compliant for FIM/FIA track marking paint.

SAFETY:

Products are intended for industrial use only, improper handling and misuse may be hazardous. Please refer to the Material Safety Data Sheets for more detail safety information.

NOTE:

This information is based on technical data that we believe to be accurate and reliable and is intended to be used by persons having the knowledge and skill to apply these coating properly. We assume no responsibility for results or damages incurred from their use by the Buyer in whole or in part.

Main Office:

P.O. Box 29139,
Portland, OR 97296-9139
PH. 503-227-6427 FAX 503-227-1609
TOLL FREE 800-924-7874
www.drewpaints.com



Date: Oct. 2017
09NS Series

Track Marking Coatings